

ADS 350 Portable Wireless Amplifier 30W



- A very competitive price
- 30 watt output
- Long-life lightweight lithium battery
- Battery charging during mains use
- Battery can be removed and recharged in a separate (optional) charger. An (optional) spare battery purchase thus allows the unit to be always available for battery use
- UHF single or (optional) dual channel receiver with 16 user selectable frequencies with 16 selectable channels (863-865 MHz)
- Mix out / AUX in (Tape / CD) jack sockets
- Optional USB interface for MP3 players
- Optional digital echo effect
- Tone controls

Technical Specifications

Speaker	5.25" 4Ω full range speaker
Receiver Module	UHF PLL single or dual channel with 16 user selectable frequencies
Carrier Frequency Range	UHF 863-865 MHz
Output power	30W rms
Optional	Tape or CD player via AUX in jack socket MP3 player via USB socket Lithium battery recharger
Charging Time	Approximately 4 to 5 hours
Operating Time	Approximately 6 to 8 hrs continuous use, depending on volume level used
Power Supply	100~240V ac / 19.5V dc 2300mA switching power supply or battery use
Rechargeable Battery	One 14.4V / 2.9Ah removable lithium battery
Frame Material	Plastic and steel
Dimensions	210(H) x 160(W) x 290(D) mm
Weight	2.2kg with battery installed